

# MINO 60 S CIRCLE

## 1500 direct / indirect

suspended  
034-741163GH




Project / Type	
Notes	
Count / Date	




Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; flat design; suspended luminaire with 1500mm cable suspension (canopy central); height adjustment without tools; incl. feed (white); surface grey powder coated; extruded profile for improved thermal management; light colour 4000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 80$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; direct/indirect light emission for additional accentuation of the ceiling; indirect light component with integrated PC boards and high quality lens system for maximum, homogeneous ceiling illumination; degree of protection IP20; PC1; 220-240 V; incl. DALI-2 converter; converter included in canopy; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

### Light distribution



### Product drawing



### General

Ceiling , Suspended	
grey , RAL 9006 <sup>1</sup>	
IP20	
indirect 5800 lm	
direct 10300 lm	
total 16100 lm	

### LED

4000 K	
CRI $\geq 80$	
L90 / 50000 h	
initial MacAdam $\leq 3$ SDCM	
MR 0.72	
MDER 0.65	

### Optical

High Performance Opal	
opal (lambertsch)	
PstLM $\leq 1.0$ <sup>2</sup>	
SVM $\leq 0.4$ <sup>2</sup>	

### Electrical

DALI-2	
220-240 V	
system 119 W	
system 135 lm/W <sup>3</sup>	
PC1	
5 DALI Addr.	

### Physical

cable 1500 mm / canopy central	
diameter 1560 mm	
height 60 mm	
centerline radius 750 mm	

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

### Installation instructions



### Lighting calculator

