

# MINO 60 S CIRCLE

## 1500 direct / indirect

suspended

034-741153XH




Project / Type	
Notes	
Count / Date	




Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; flat design; suspended luminaire with 1500mm cable suspension (canopy central); height adjustment without tools; incl. feeder cable; surface special colours powder coated; extruded profile for improved thermal management; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 80$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; direct/indirect light emission for additional accentuation of the ceiling; indirect light component with integrated PC boards and high quality lens system for maximum, homogeneous ceiling illumination; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; incl. DALI-2 converter; converter included in canopy; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

### Light distribution



### Product drawing



### General

Ceiling , Suspended	
special colours	
IP20	
indirect 5100 lm	
direct 9010 lm	
total 14110 lm	

### LED

3000 K	
CRI $\geq 80$	
L90 / 50000 h	
photobio. safety RG 0 - no Risk	
initial MacAdam $\leq 3$ SDCM	
MR 0.56	
MDER 0.51	

### Optical

High Performance Opal	
PstLM $\leq 1.0$ <sup>1</sup>	
SVM $\leq 0.4$ <sup>1</sup>	

### Electrical

DALI-2	
119 W	
PC1 220-240V	
119 lm/W	
5 DALI Addr.	

### Physical

cable 1500 mm / canopy central	
length 1560 mm	
width 60 mm	
height 60 mm	
centerline radius 750 mm	
14 kg	

<sup>1</sup> Value of containing product at full load (undimmed)

### Lighting calculator

