

MINO 60 S CIRCLE

1500 direct / indirect

suspended

034-7411538H



Project / Type	
Notes	
Count / Date	



Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; flat design; suspended luminaire with 1500mm cable suspension (canopy central); height adjustment without tools; incl. feed (black); surface black powder coated; extruded profile for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; direct/indirect light emission for additional accentuation of the ceiling; indirect light component with integrated PC boards and high quality lens system for maximum, homogeneous ceiling illumination; degree of protection IP20; PC1; 220-240 V; incl. DALI-2 converter; converter included in canopy; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;



General

Ceiling Suspended	
black RAL 9005 ¹	
IP20	
indirect 5100 lm direct 9010 lm	
total 14110 lm	

LED

3000 K	
CRI ≥ 80	
L90 / 50000 h	
initial MacAdam ≤ 3 SDCM	
MR 0.56 MDER 0.51	

Optical

High Performance Opal opal (lambertsch)	
PstLM ≤ 1.0 ² SVM ≤ 0.4 ²	

Electrical


DALI-2 5 DALI Addr.	
PC1 220-240 V	
system 119 W	
system 119 lm/W ³	

Physical


cable 1500 mm / canopy central	
diameter 1560 mm height 60 mm	
centerline radius 750 mm	
10.7 kg	

¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Light distribution



Product drawing



Installation instructions



Lighting calculator

