

MINO 60 S CIRCLE

1500 direct

suspended

034-741063GH



Project / Type _____


Notes _____

Count / Date _____




Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; flat design; suspended luminaire with 1500mm cable suspension (canopy central); height adjustment without tools; incl. feed (white); surface grey powder coated; extruded profile for improved thermal management; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; degree of protection IP20; PC1; 220-240 V; incl. DALI-2 converter; converter included in canopy; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Suspended _____
grey , RAL 9006 ¹ _____
IP20 _____
10300 lm _____

LED

4000 K _____
CRI ≥ 80 _____
L90 / 50000 h _____
initial MacAdam ≤ 3 SDCM _____
MR 0.72 _____
MDER 0.65 _____

Optical

High Performance Opal _____
opal (lambertsch) _____
PstLM ≤ 1.0 ² _____
SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____
220-240 V _____
system 83 W _____
system 124 lm/W³ _____
PC1 _____
1 DALI Addr. _____

Physical

cable 1500 mm / canopy central _____
diameter 1560 mm _____
height 60 mm _____
centerline radius 750 mm _____

¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses
& operating device efficiency

Installation instructions



Lighting calculator

