

MINO 60 S CIRCLE

1000 direct / indirect

suspended

034-721353XH




Project / Type	
Notes	
Count / Date	




Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; flat design; suspended luminaire with 1500mm cable suspension; height adjustment without tools; incl. feed (white); surface special colours powder coated; extruded profile for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; direct/indirect light emission for additional accentuation of the ceiling; indirect light component with integrated PC boards and high quality lens system for maximum, homogeneous ceiling illumination; degree of protection IP20; PC1; 220-240 V; incl. DALI-2 converter; converter included in canopy; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling Suspended	
special colours	
IP20	
indirect 3120 lm direct 6420 lm	
total 9540 lm	

LED

3000 K	
CRI ≥ 80	
L90 / 50000 h	
initial MacAdam ≤ 3 SDCM	
MR 0.56 MDER 0.51	

Optical

High Performance Opal opal (lambertsch)	
PstLM ≤ 1.0 ¹ SVM ≤ 0.4 ¹	

Electrical

DALI-2 2 DALI Addr.	
PC1 220-240 V	
system 79 W	
system 121 lm/W ²	

Physical

cable 1500 mm	
diameter 1060 mm height 60 mm	
centerline radius 500 mm	

¹ Value of containing product at full load (undimmed)
² incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Lighting calculator

