

# MINO 60 S CIRCLE

## 1500 direct

suspended

034-7210638H



Project / Type \_\_\_\_\_


Notes \_\_\_\_\_

Count / Date \_\_\_\_\_




Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; flat design; suspended luminaire with 1500mm cable suspension; height adjustment without tools; incl. feeder cable; surface black powder coated; extruded profile for improved thermal management; light colour 4000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 80$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; incl. DALI-2 converter; converter included in canopy; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

### Light distribution



### Product drawing



### General

Ceiling , Suspended  
black , RAL9005 <sup>1</sup>  
IP20  
10300 lm

### LED

4000 K  
CRI  $\geq 80$   
L90 / 50000 h  
photobio. safety RG 0 - no Risk  
initial MacAdam  $\leq 3$  SDCM  
MR 0.72  
MDER 0.65

### Optical

High Performance Opal  
PstLM  $\leq 1.0$  <sup>2</sup>  
SVM  $\leq 0.4$  <sup>2</sup>

### Electrical

DALI-2  
88 W  
PC1 220-240V  
117 lm/W  
1 DALI Addr.

### Physical

cable 1500 mm  
length 1560 mm  
width 60 mm  
height 60 mm  
centerline radius 750 mm  
12.4 kg

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

### Lighting calculator

