


# BO 45 base surface 2 lamps

049-643071XS



Project / Type \_\_\_\_\_  
 Notes \_\_\_\_\_  
 Count / Date \_\_\_\_\_



## General

Ceiling , Surface \_\_\_\_\_  
 tilt max 90° \_\_\_\_\_  
 rotation 330° \_\_\_\_\_  
 special colours \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 2060 lm \_\_\_\_\_

## LED

3500 K \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_  
 L80 / 50000 h \_\_\_\_\_  
 initial MacAdam ≤ 2 SDCM \_\_\_\_\_  
 R<sub>g</sub>: 97 , R<sub>f</sub>: 90 , R<sub>f(1-15)</sub>: 89 \_\_\_\_\_  
 MR 0.7 \_\_\_\_\_  
 MDER 0.63 \_\_\_\_\_

## Optical

spot \_\_\_\_\_  
 beam angle 12° \_\_\_\_\_

## Electrical


non DIM \_\_\_\_\_  
 30 W \_\_\_\_\_  
 PC1 220-240V \_\_\_\_\_  
 69 lm/W \_\_\_\_\_

## Physical

length 245 mm \_\_\_\_\_  
 width 55 mm \_\_\_\_\_  
 height 164 mm \_\_\_\_\_  
 0.7 kg \_\_\_\_\_

Surface mounted spotlight made of aluminium; 2 lamps; cylindrical spotlight heads; surface special colours powder coated; 330° rotatable and 90° tiltable; surface mounted housing in aluminium incl. converter; mounting plate with pre-assembled converter unit can be pre-mounted; luminaire housing can be attached without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3500 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality, aluminium, vapour deposition coated reflector with faceted lens design; precise radiation characteristic with 12° beam; good glare control through recessed light point level; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC1 220-240V; incl. converter, non dimmable; luminaire for through wiring; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


## Light distribution



spot 12°

h (m)	E0° (lx)	ø (m)
1	13000	0.21
2	3300	0.42
3	1400	0.63
4	800	0.84
5	500	1.06

## Product drawing



## Installation instructions



## Lighting calculator

