

# TWIST 100

trim

048-1121018M 048-2796318 002-90789



Project / Type
Notes
Count / Date



220-240V
360°
X-PERT
X-PERT

<b>General</b>
Ceiling , Recessed
tilt max 45°
rotation 360°
black , RAL9005 <sup>1</sup>
Mounting set jet black
front IP20 , back IP20
3150 lm


<b>LED</b>
3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM

<b>Optical</b>
medium
beam angle 27°
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

<b>Electrical</b>
DALI-2
25.3 W
PC2 220-240V
125 lm/W
1 DALI Addr.


<b>Physical</b>
diameter 118 mm
height 99 mm
0.66 kg

## Light distribution



medium 27°		
h (m)	E0° (lx)	ø (m)
1	10100	0.49
2	2500	0.97
3	1100	1.46
4	600	1.95
5	400	2.43

## Product drawing



<b>Cutout</b>
diameter 108 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 160 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

### Installation instructions

### Lighting calculator