

# INDIRECT low power

MOVE IT PRO  
086-6880730B



Project / Type

Notes

Count / Date



Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush with profile system; power supplied via MOVE IT PRO system track profile; with indirect light component for additional accentuation of the ceiling; high quality lens system for maximum, homogeneous ceiling illumination; passive cooling of the LEDs through improved heat sink geometry; light colour 3500 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 80$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC2 220-240V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;



General

Ceiling , Track

indirect batwing low power

white

1630 lm/m

IP20

7190 lm

LED

3500 K

CRI  $\geq 80$

L90 / 50000 h

initial MacAdam  $\leq 3$  SDCM

Optical

batwing

UGR < 10 ,  $\geq 65^\circ$  <1500 cd/m<sup>2</sup>

Electrical

DALI-2

47 W

PC2 220-240V

153 lm/W

1 DALI Addr.

11 W/m


Physical

length 4500 mm

width 24 mm

height 6 mm

## Light distribution



## Product drawing



## Lighting calculator

