

INDIRECT low power

MOVE IT PRO

086-6880530B



Project / Type

Notes

Count / Date



General

Ceiling | Track
indirect batwing low power
white
IP20
6720 lm
1540 lm/m

LED

3000 K
CRI \geq 80
L90 / 50000 h
initial MacAdam \leq 3 SDCM
MR 0.56 | MDER 0.51

Optical

batwing
UGR \leq 10 | \geq 65° <1500 cd/m²

Electrical


DALI-2 | 1 DALI Addr.
PC2 | 220-240 V
system 47 W
system 143 lm/W¹
11 W/m

Physical

length 4412 mm | width 24 mm | height 6 mm

Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush with profile system; power supplied via MOVE IT PRO system track profile; with indirect light component for additional accentuation of the ceiling; high quality lens system for maximum, homogeneous ceiling illumination; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC2; 220-240 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Lighting calculator

