

# MOVE IN 45 flex round

trim

063-8221518V 063-8822117 002-90729



Project / Type

Notes

Count / Date



## General

Ceiling | Semi-Recessed  
tilt max 90°  
rotation 360°  
jet black | RAL 9005 <sup>1</sup>  
Mounting set traffic white  
IP20  
346 lm  
fixture 50 lm/W <sup>2</sup>

## LED

3000 K  
CRI ≥ 90  
L85 / 50000 h  
initial MacAdam ≤ 3 SDCM  
R<sub>g</sub>: 98 | R<sub>f</sub>: 91 | R<sub>f(1-15)</sub>: 89  
MR 0.6 | MDER 0.55

## Optical

super spot | beam angle 8°  
PstLM ≤ 1.0 <sup>3</sup> | SVM ≤ 0.4 <sup>3</sup>


## Electrical

DALI-2 | 1 DALI Addr.  
PC2 | 220-240 V  
system 9.2 W | fixture 6.9 W  
11 Vf | 600 mA

## Physical

trim  
diameter 77 mm | height 107 mm  
0.59 kg


## Light distribution



super spot 8°

h (m)	E0° (lx)	ø (m)
1	12100	0.14
2	3000	0.28
3	1300	0.41
4	800	0.55
5	500	0.69

## Product drawing



## Cutout

diameter 65 mm  
min. ceiling thickness 2 mm | max. ceiling thickness 25 mm  
recessed depth 195 mm

<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses  
<sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

