

# MOVE IN 45 flex round

trim

063-8221517F 063-8822117 002-90728



Project / Type

Notes

Count / Date



220-240V

General

Ceiling , Semi-Recessed

tilt max 90°

rotation 360°

white , RAL9016 <sup>1</sup>

Mounting set traffic white

IP20

1310 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-5)</sub>: 88

MR 0.59

MDER 0.53

Optical

flood

beam angle 36°

P<sub>stLM</sub> ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

Electrical

DALI-2

15.9 W

PC2 220-240V

82 lm/W

1 DALI Addr.

Physical

trim

diameter 77 mm

height 107 mm

0.4 kg

Cutout

diameter 65 mm


min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 195 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)



## Light distribution



flood 36°

h (m)	E0° (lx)	ø (m)
1	3900	0.65
2	980	1.29
3	430	1.94
4	240	2.59
5	160	3.23

## Product drawing



## Installation instructions



## Lighting calculator

