

# MOVE IN 45 flex round

trimless

063-8221517F 063-8812117 002-90728



Project / Type

Notes

Count / Date



## General

Ceiling , Semi-Recessed

tilt max 90°

rotation 360°

white , RAL 9016 <sup>1</sup>

IP20

1310 lm

## LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f1-15</sub>: 89

MR 0.59

MDER 0.53

## Optical

flood

beam angle 36°

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2

220-240 V

system 15.9 W

fixture 13.5 W

fixture 97 lm/W<sup>3</sup>

36 Vf

400 mA

PC2

1 DALI Addr.

## Physical

trimless

diameter 75 mm

height 106 mm

0.53 kg

## Cutout

diameter 65 mm

min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 195 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. consideration of optical losses & internal control unit losses

## Light distribution



flood 36°

h (m)	E0° (lx)	ø (m)
1	3900	0.65
2	980	1.29
3	430	1.94
4	240	2.59
5	160	3.23

## Product drawing



## Installation instructions



## Lighting calculator

