

MOVE IN 45 flex round

trim

063-8221514V 063-8822118 002-90729



Project / Type
Notes
Count / Date



General
Ceiling , Semi-Recessed
tilt max 90°
rotation 360°
chrome
Mounting set jet black
IP20
346 lm
fixture 50 lm/W ¹

LED
3000 K
CRI ≥ 90
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 98 , R _r : 91 , R _{t(1-15)} : 89
MR 0.6
MDER 0.55

Optical
super spot
beam angle 8°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²


Electrical
DALI-2
220-240 V
system 9.2 W
fixture 6.9 W
11 Vf
600 mA
PC2
1 DALI Addr.

Physical
trim
diameter 77 mm
height 107 mm
0.59 kg

Cutout
diameter 65 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 195 mm


¹ incl. consideration of optical losses & internal control unit losses
² Value of containing product at full load (undimmed)

Light distribution



super spot 8°		
h (m)	E0° (lx)	ø (m)
1	12100	0.14
2	3000	0.28
3	1300	0.41
4	800	0.55
5	500	0.69

Product drawing



Installation instructions

Lighting calculator