

MOVE IN 45 flex round

trimless

063-8221418V 063-8812117 002-90729



Project / Type

Notes

Count / Date



General

Ceiling Semi-Recessed
tilt max 90°
rotation 360°
black RAL 9005 ¹
Mounting set traffic white
IP20
406 lm
fixture 59 lm/W ²

LED

2700 K
CRI ≥ 90
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 99 R _r : 91 R _(f-15) : 89
MR 0.54 MDER 0.49

Optical

super spot beam angle 8°
PstLM ≤ 1.0 ³ SVM ≤ 0.4 ³


Electrical

DALI-2 1 DALI Addr.
PC2 220-240 V
system 9.2 W fixture 6.9 W
11 Vf 600 mA

Physical

trimless
diameter 75 mm height 106 mm
0.53 kg


Light distribution



super spot 8°

h (m)	E0° (lx)	ø (m)
1	14200	0.14
2	3500	0.28
3	1600	0.41
4	900	0.55
5	600	0.69

Product drawing



Cutout

diameter 65 mm
min. ceiling thickness 9 mm max. ceiling thickness 25 mm
recessed depth 195 mm

¹ RAL code
² incl. consideration of optical losses & internal control unit losses
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

