

# MOVE IN 45 flex round

trimless

063-8221418S 063-8812117 002-90720



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Semi-Recessed  
 tilt max 90°  
 rotation 360°  
 black , RAL9005 <sup>1</sup>  
 Mounting set traffic white  
 IP20  
 1020 lm

## LED

2700 K  
 CRI ≥ 90  
 L80 / 50000 h  
 initial MacAdam ≤ 2 SDCM  
 R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>(1-15)</sub>: 89  
 MR 0.53  
 MDER 0.48

## Optical

spot  
 beam angle 12°  
 P<sub>stLM</sub> ≤ 1.0 <sup>2</sup>  
 SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2  
 14.5 W  
 PC2 220-240V  
 70 lm/W  
 1 DALI Addr.

## Physical

trimless  
 diameter 75 mm  
 height 106 mm  
 0.45 kg


## Cutout

diameter 65 mm  
 min. ceiling thickness 9 mm  
 max. ceiling thickness 25 mm  
 recessed depth 195 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

Round spotlight element in aluminium; surface black powder coated; installation without tools in mounting set due to patented ball catch system; for trimless installation in plasterboard ceilings; suitable for ceiling thickness of 9-25 mm; special mounting tool for easy installation of the trimless housing available as an accessory; spotlight element height adjustable without tools: flush with the ceiling, or extended 25 mm or 35 mm; 360° rotatable and 90° tiltable; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality, aluminium, vapour deposition coated reflector with faceted lens design; precise radiation characteristic with 12° beam; good glare control through recessed light point level; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC2 220-240V; incl. DALI-2 converter; converter wired secondary side; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;



## Light distribution



spot 12°

h (m)	E0° (lx)	ø (m)
1	12900	0.21
2	3200	0.42
3	1400	0.63
4	800	0.84
5	500	1.06

## Product drawing



## Installation instructions



## Lighting calculator

