

# MOVE IN 45 round

trim

063-8121518M 063-8822117 002-90728



Project / Type

Notes

Count / Date



### General

Ceiling , Semi-Recessed

black , RAL9005 <sup>1</sup>

Mounting set traffic white

IP20

1270 lm

### LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 88

MR 0.59

MDER 0.53

### Optical

medium

beam angle 24°

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

### Electrical

DALI-2

15.9 W

PC2 220-240V

80 lm/W

1 DALI Addr.

### Physical

trim

diameter 77 mm

height 107 mm

0.39 kg

### Cutout

diameter 65 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 195 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

### Light distribution



h (m)	E0° (lx)	ø (m)
1	6120	0.43
2	1530	0.86
3	680	1.30
4	380	1.73
5	240	2.16

### Product drawing



### Installation instructions



### Lighting calculator

