

# MOVE IN 45 round

trim

063-8121517V 063-8822117 002-90729



Project / Type

Notes

Count / Date



## General

Ceiling , Semi-Recessed  
white , RAL9016 <sup>1</sup>  
Mounting set traffic white  
IP20  
346 lm

## LED

3000 K  
CRI ≥ 90  
L85 / 50000 h  
initial MacAdam ≤ 3 SDCM  
R<sub>g</sub>: 98 , R<sub>r</sub>: 91 , R<sub>(1-15)</sub>: 89  
MR 0.6  
MDER 0.55

## Optical

super spot  
beam angle 8°  
PstLM ≤ 1.0 <sup>2</sup>  
SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2  
9.2 W  
PC2 220-240V  
38 lm/W  
1 DALI Addr.

## Physical

trim  
diameter 77 mm  
height 107 mm  
0.29 kg

## Cutout

diameter 65 mm  
min. ceiling thickness 2 mm  
max. ceiling thickness 25 mm  
recessed depth 195 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



super spot 8°

h (m)	E0° (lx)	ø (m)
1	12100	0.14
2	3000	0.28
3	1300	0.41
4	800	0.55
5	500	0.69

## Product drawing



## Installation instructions



## Lighting calculator

