

# MOVE IN 45 round

trim

063-8121414F 063-8822118 002-90728



Project / Type \_\_\_\_\_  
 Notes \_\_\_\_\_  
 Count / Date \_\_\_\_\_



## General

Ceiling , Semi-Recessed \_\_\_\_\_  
 chrome \_\_\_\_\_  
 Mounting set jet black \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 1230 lm \_\_\_\_\_

## LED

2700 K \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_  
 L80 / 50000 h \_\_\_\_\_  
 initial MacAdam ≤ 2 SDCM \_\_\_\_\_  
 R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_  
 MR 0.53 \_\_\_\_\_  
 MDER 0.48 \_\_\_\_\_

## Optical

flood \_\_\_\_\_  
 beam angle 36° \_\_\_\_\_  
 PstLM ≤ 1.0 <sup>1</sup> \_\_\_\_\_  
 SVM ≤ 0.4 <sup>1</sup> \_\_\_\_\_

## Electrical

DALI-2 \_\_\_\_\_  
 15.9 W \_\_\_\_\_  
 PC2 220-240V \_\_\_\_\_  
 77 lm/W \_\_\_\_\_  
 1 DALI Addr. \_\_\_\_\_

## Physical


trim \_\_\_\_\_  
 diameter 77 mm \_\_\_\_\_  
 height 107 mm \_\_\_\_\_  
 0.38 kg \_\_\_\_\_

## Cutout

diameter 65 mm \_\_\_\_\_  
 min. ceiling thickness 2 mm \_\_\_\_\_  
 max. ceiling thickness 25 mm \_\_\_\_\_  
 recessed depth 195 mm \_\_\_\_\_

<sup>1</sup> Value of containing product at full load (undimmed)



## Light distribution



flood 36°

h (m)	E0° (lx)	ø (m)
1	3660	0.65
2	920	1.29
3	410	1.94
4	230	2.59
5	150	3.23

## Product drawing



## Installation instructions



## Lighting calculator

