

# MOVE IN 45 round

trimless

063-8121517M 063-8812117 002-90728



Project / Type

Notes

Count / Date



### General

Ceiling , Semi-Recessed

white , RAL9016 <sup>1</sup>

Mounting set traffic white

IP20

1270 lm

### LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 88

MR 0.59

MDER 0.53

### Optical

medium

beam angle 24°

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

### Electrical

DALI-2

15.9 W

PC2 220-240V

80 lm/W

1 DALI Addr.

### Physical

trimless

diameter 75 mm

height 106 mm

0.5 kg

### Cutout

diameter 65 mm


min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 195 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)


### Light distribution



medium 24°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 6120     | 0.43  |
| 2     | 1530     | 0.86  |
| 3     | 680      | 1.30  |
| 4     | 380      | 1.73  |
| 5     | 240      | 2.16  |

### Product drawing



### Installation instructions



### Lighting calculator

