

# MOVE IN 45 round

trim

063-8121516V 063-8822118 002-90729



Project / Type

Notes

Count / Date



### General

Ceiling , Semi-Recessed

brushed aluminium

Mounting set jet black

IP20

346 lm

### LED

3000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 98 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89

MR 0.6

MDER 0.55

### Optical

super spot

beam angle 8°

PstLM ≤ 1.0 <sup>1</sup>

SVM ≤ 0.4 <sup>1</sup>

### Electrical

DALI-2

9.2 W

PC2 220-240V

38 lm/W

1 DALI Addr.

### Physical

trim

diameter 77 mm

height 107 mm

0.28 kg

### Cutout

diameter 65 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 195 mm

<sup>1</sup> Value of containing product at full load (undimmed)

### Light distribution



super spot 8°

h (m)	E0° (lx)	ø (m)
1	12100	0.14
2	3000	0.28
3	1300	0.41
4	800	0.55
5	500	0.69

### Product drawing



### Installation instructions



### Lighting calculator

