

# MOVE IN 45 round

trimless

063-8121516S 063-8812117 002-90720



Project / Type

Notes

Count / Date



### General

Ceiling , Semi-Recessed

brushed aluminium

Mounting set traffic white

IP20

1080 lm

### LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 88

MR 0.59

MDER 0.53

### Optical

spot

beam angle 12°

PstLM ≤ 1.0 <sup>1</sup>

SVM ≤ 0.4 <sup>1</sup>

### Electrical

DALI-2

14.5 W

PC2 220-240V

74 lm/W

1 DALI Addr.

### Physical

trimless

diameter 75 mm

height 106 mm

0.26 kg

### Cutout

diameter 65 mm


min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 195 mm

<sup>1</sup> Value of containing product at full load (undimmed)

### Light distribution



spot 12°

h (m)	E0° (lx)	ø (m)
1	13700	0.21
2	3400	0.42
3	1500	0.63
4	900	0.84
5	500	1.06

### Product drawing



### Installation instructions



### Lighting calculator

