

# MOVE IN 45 round

trim

063-8121516F 063-8822117 002-90728



Project / Type

Notes

Count / Date



## General

Ceiling | Semi-Recessed  
brushed aluminium  
Mounting set traffic white  
IP20  
1310 lm

## LED

3000 K  
CRI  $\geq 90$   
L80 / 50000 h  
initial MacAdam  $\leq 2$  SDCM  
R<sub>g</sub>: 100 | R<sub>f</sub>: 91 | R<sub>(1-15)</sub>: 89  
MR 0.59 | MDER 0.53

## Optical

flood | beam angle 36°  
PstLM  $\leq 1.0$ <sup>1 2 3 4</sup> | SVM  $\leq 0.4$ <sup>1 2 3 4</sup>

## Electrical

DALI-2 | 1 DALI Addr.  
PC2 | 220-240 V  
system 15.9 W | fixture 13.5 W  
fixture 97 lm/W<sup>5</sup>  
36 Vf | 400 mA


## Physical

trim  
diameter 77 mm | height 107 mm  
0.59 kg

## Cutout

diameter 65 mm  
min. ceiling thickness 2 mm | max. ceiling  
thickness 25 mm  
recessed depth 195 mm


## Light distribution



flood 36°

h (m)	E0° (lx)	ø (m)
1	3900	0.65
2	980	1.29
3	430	1.94
4	240	2.59
5	160	3.23

## Product drawing



<sup>1</sup> oval lens BO 45 007-1965880 <sup>2</sup> soft lens BO 45 007-1965980  
<sup>3</sup> wallwasher lens BO 45 007-1965780  
<sup>4</sup> Value of containing product at full load (undimmed)  
<sup>5</sup> incl. consideration of optical losses & internal control unit losses

## Installation instructions



## Lighting calculator

