

# MOVE IN 45 round

trim

063-8121514V 063-8822118 002-90729



Project / Type

Notes

Count / Date



## General

Ceiling , Semi-Recessed

chrome

Mounting set jet black

IP20

346 lm

## LED

3000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 98 , R<sub>r</sub>: 91 , R<sub>{1-15}</sub>: 89

MR 0.6

MDER 0.55

## Optical

super spot

beam angle 8°

PstLM ≤ 1.0 <sup>1</sup>

SVM ≤ 0.4 <sup>1</sup>

## Electrical

DALI-2

9.2 W

PC2 220-240V

38 lm/W

1 DALI Addr.

## Physical

trim

diameter 77 mm

height 107 mm

0.28 kg

## Cutout

diameter 65 mm

min. ceiling thickness 2 mm


max. ceiling thickness 25 mm

recessed depth 195 mm

<sup>1</sup> Value of containing product at full load (undimmed)

Round spotlight element in aluminium; surface chrome; installation without tools in mounting set due to patented ball catch system; recessed light with trim jet black; suitable for ceiling thickness of 2-25 mm; spotlight element height adjustable without tools: flush with the ceiling, or extended 25 mm or 35 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality, aluminium, vapour deposition coated reflector with faceted lens design; precise radiation characteristic with 8° beam; good glare control through recessed light point level; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC2 220-240V; incl. DALI-2 converter; converter wired secondary side; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


## Light distribution



super spot 8°

h (m)	E0° (lx)	ø (m)
1	12100	0.14
2	3000	0.28
3	1300	0.41
4	800	0.55
5	500	0.69

## Product drawing



## Installation instructions



## Lighting calculator

