

MOVE IN 45 round

trim

063-8121514M 063-8822118 002-90728



Project / Type

Notes

Count / Date



General

Ceiling , Semi-Recessed

chrome

Mounting set jet black

IP20

1270 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 100 , R_f: 91 , R_{f(1-15)}: 88

MR 0.59

MDER 0.53

Optical

medium

beam angle 24°

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Electrical

DALI-2

15.9 W

PC2 220-240V

80 lm/W

1 DALI Addr.

Physical

trim

diameter 77 mm

height 107 mm

0.38 kg

Cutout

diameter 65 mm


min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 195 mm

¹ Value of containing product at full load (undimmed)

Light distribution



medium 24°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 6120 | 0.43 |
| 2 | 1530 | 0.86 |
| 3 | 680 | 1.30 |
| 4 | 380 | 1.73 |
| 5 | 240 | 2.16 |

Product drawing



Installation instructions



Lighting calculator

