

# MOVE IN 45 round

trim

063-8121418V 063-8822117 002-90729



Project / Type

Notes

Count / Date



### General

Ceiling , Semi-Recessed

black , RAL9005 <sup>1</sup>

Mounting set traffic white

IP20

400 lm

### LED

2700 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89

MR 0.54

MDER 0.49

### Optical

super spot

beam angle 8°

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

### Electrical

DALI-2

9.2 W

PC2 220-240V

43 lm/W

1 DALI Addr.

### Physical

trim

diameter 77 mm

height 107 mm

0.49 kg

### Cutout

diameter 65 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 195 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)


### Light distribution



super spot 8°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 14000    | 0.14  |
| 2     | 3500     | 0.28  |
| 3     | 1600     | 0.41  |
| 4     | 900      | 0.55  |
| 5     | 600      | 0.69  |

### Product drawing



### Installation instructions



### Lighting calculator

