

MOVE IN 45 round

trimless

063-8121417M 063-8812117 002-90728



Project / Type

Notes

Count / Date



General

Ceiling , Semi-Recessed

white , RAL 9016 ¹

IP20

1200 lm

fixture 89 lm/W²

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89

MR 0.53

MDER 0.48

Optical

medium

beam angle 24°

PstLM ≤ 1.0 ³

SVM ≤ 0.4 ³

Electrical

DALI-2

220-240 V

system 15.9 W

fixture 13.5 W

36 V_f

400 mA

PC2

1 DALI Addr.

Physical

trimless

diameter 75 mm

height 106 mm

0.53 kg

Cutout


diameter 65 mm

min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 195 mm


Light distribution



medium 24°

h (m)	E0° (lx)	ø (m)
1	5780	0.43
2	1440	0.86
3	640	1.30
4	360	1.73
5	230	2.16

Product drawing



¹ RAL code

² incl. consideration of optical losses & internal control unit losses

³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

