

MOVE IN 45 round

trim

063-8121416S 063-8822117 002-90720



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Semi-Recessed
brushed aluminium
Mounting set traffic white
IP20
1020 lm

LED

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
 $R_g: 99, R_r: 91, R_{(1-15)}: 89$
MR 0.53
MDER 0.48

Optical

spot
beam angle 12°
 $PstLM \leq 1.0^1$
 $SVM \leq 0.4^1$

Electrical

DALI-2
14.5 W
PC2 220-240V
70 lm/W
1 DALI Addr.

Physical


trim
diameter 77 mm
height 107 mm
0.49 kg

Cutout

diameter 65 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 195 mm

¹ Value of containing product at full load (undimmed)

Light distribution



spot 12°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 12900 | 0.21 |
| 2 | 3200 | 0.42 |
| 3 | 1400 | 0.63 |
| 4 | 800 | 0.84 |
| 5 | 500 | 1.06 |

Product drawing



Installation instructions



Lighting calculator

