

# MOVE IN 45 round

trim

063-8121416F 063-8822117 002-90728



Project / Type

Notes

Count / Date



### General

Ceiling , Semi-Recessed

brushed aluminium

Mounting set traffic white

IP20

1230 lm

### LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89

MR 0.53

MDER 0.48

### Optical

flood

beam angle 36°

PstLM ≤ 1.0 <sup>1</sup>

SVM ≤ 0.4 <sup>1</sup>

### Electrical

DALI-2

15.9 W

PC2 220-240V

77 lm/W

1 DALI Addr.

### Physical

trim

diameter 77 mm

height 107 mm

0.39 kg

### Cutout

diameter 65 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 195 mm

<sup>1</sup> Value of containing product at full load (undimmed)

### Light distribution



flood 36°

h (m)	E0° (lx)	ø (m)
1	3660	0.65
2	920	1.29
3	410	1.94
4	230	2.59
5	150	3.23

### Product drawing



### Installation instructions



### Lighting calculator

