

# MOVE IN 45 round

trimless

063-8121414V 063-8812117 002-90729



Project / Type \_\_\_\_\_  
 Notes \_\_\_\_\_  
 Count / Date \_\_\_\_\_



## General

Ceiling , Semi-Recessed \_\_\_\_\_  
 chrome \_\_\_\_\_  
 Mounting set traffic white \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 400 lm \_\_\_\_\_

## LED

2700 K \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_  
 L85 / 50000 h \_\_\_\_\_  
 initial MacAdam ≤ 3 SDCM \_\_\_\_\_  
 R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_  
 MR 0.54 \_\_\_\_\_  
 MDER 0.49 \_\_\_\_\_

## Optical

super spot \_\_\_\_\_  
 beam angle 8° \_\_\_\_\_  
 PstLM ≤ 1.0 <sup>1</sup> \_\_\_\_\_  
 SVM ≤ 0.4 <sup>1</sup> \_\_\_\_\_

## Electrical

DALI-2 \_\_\_\_\_  
 9.2 W \_\_\_\_\_  
 PC2 220-240V \_\_\_\_\_  
 43 lm/W \_\_\_\_\_  
 1 DALI Addr. \_\_\_\_\_

## Physical


trimless \_\_\_\_\_  
 diameter 75 mm \_\_\_\_\_  
 height 106 mm \_\_\_\_\_  
 0.46 kg \_\_\_\_\_

## Cutout

diameter 65 mm \_\_\_\_\_  
 min. ceiling thickness 9 mm \_\_\_\_\_  
 max. ceiling thickness 25 mm \_\_\_\_\_  
 recessed depth 195 mm \_\_\_\_\_

<sup>1</sup> Value of containing product at full load (undimmed)



## Light distribution



super spot 8°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 14000    | 0.14  |
| 2     | 3500     | 0.28  |
| 3     | 1600     | 0.41  |
| 4     | 900      | 0.55  |
| 5     | 600      | 0.69  |

## Product drawing



## Installation instructions



## Lighting calculator

