

INDIRECT EXTENSION

low power MOVE IT PRO

086-6800730B



Project / Type

Notes

Count / Date



Linear light inset made of plastic; light inset can be installed flexibly and without tools; flush with profile system; power supplied via INDIRECT MOVE IT PRO inset; with indirect light component for additional accentuation of the ceiling; high quality lens system for maximum, homogeneous ceiling illumination; passive cooling of the LEDs through improved heat sink geometry; light colour 3500 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Track Suspended

low power

white

IP20

399 lm

LED

3500 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.62

MDER 0.57

Optical

batwing

UGR ≤ 10 , $\geq 65^\circ$ <1500 cd/m²

Electrical

system 2.8 W

fixture 2.4 W

system 143 lm/W¹

50 mA

PC3

Physical

length 245 mm

width 24 mm

height 6 mm

¹ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Lighting calculator

