

INDIRECT EXTENSION

low power MOVE IT PRO

086-6800530B



Project / Type _____


Notes _____

Count / Date _____



Linear light inset made of plastic; light inset can be installed flexibly and without tools; flush with profile system; power supplied via INDIRECT MOVE IT PRO inset; with indirect light component for additional accentuation of the ceiling; high quality lens system for maximum, homogeneous ceiling illumination; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Track Suspended _____

low power _____

white _____

IP20 _____

374 lm _____

LED

3000 K _____

CRI ≥ 80 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

MR 0.56 _____

MDER 0.51 _____

Optical

batwing _____

UGR ≤ 10 , $\geq 65^\circ$ <1500 cd/m² _____

Electrical

system 2.8 W _____

fixture 2.4 W _____

system 134 lm/W¹ _____

50 mA _____

PC3 _____

Physical

length 245 mm _____

width 24 mm _____

height 6 mm _____

0.04 kg _____

¹ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Lighting calculator

