

INDIRECT EXTENSION

low power MOVE IT PRO

086-6800430B



Project / Type

Notes

Count / Date



General

Ceiling | Track Suspended

white

IP20

374 lm

LED

2700 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.48 | MDER 0.44

Optical

batwing

UGR ≤ 10 | $\geq 65^\circ$ < 1500 cd/m²

Electrical

system 2.8 W | fixture 2.4 W

system 134 lm/W¹

50 mA

PC3

Physical


length 245 mm | width 24 mm | height 6 mm

0.07 kg

¹ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Linear light inset made of plastic; light inset can be installed flexibly and without tools; flush with profile system; power supplied via INDIRECT MOVE IT PRO inset; with indirect light component for additional accentuation of the ceiling; high quality lens system for maximum, homogeneous ceiling illumination; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; light source replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator

