



Project / Type _____

Notes _____

Count / Date _____



General	
Ceiling , Track	
spot line inset	
white , RAL9016 ¹	
2290 lm/m	
IP20	
5730 lm	


LED	
4000 K	
CRI ≥ 90	
L90 / 50000 h	
initial MacAdam ≤ 3 SDCM	
R _g : 99 , R _f : 92 , R ₍₁₋₁₅₎ : 90	
MR 0.81	
MDER 0.74	

Optical	
wide flood	
UGR < 16 , ≥65° <1500 cd/m ²	
PstLM ≤ 1.0 ²	
SVM ≤ 0.4 ²	

Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush with profile system; power supplied via MOVE IT PRO system track profile; surface white; fitted with single LED light points; good glare control through recessed light point level; inserted lenses with wide flood radiation characteristic; for use in schools, retail and offices; UGR ≤ 16; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC2 220-240V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Electrical	
DALI-2	
42 W	
PC2 220-240V	
136 lm/W	
1 DALI Addr.	
17 W/m	

Light distribution



Product drawing



Physical	
length 2500 mm	
width 43 mm	
height 13 mm	

¹ RAL code ² Value of containing product at full load (undimmed)

Lighting calculator

