

# VARO 110 S

track  
180-6530037F



Project / Type

Notes

Count / Date



Track light made of die-cast aluminium; surface white powder coated; 355° rotatable and 90° tiltable; integrated converter in the plastic adapter; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; including high quality aluminium reflector with spherical reflector; high gloss anodised; neutral colour reflection through absolute freedom from interference colour; for brilliant object staging; precise radiation characteristic with 40° beam; installed and exchanged without tools; optical attachments available as accessories; optical attachments can be combined; accessories are listed separately; degree of protection IP20; PC2; 220-240 V; incl. DALI-2 converter; adapter for toolless insertion or movement on a variety of 3-phase power tracks; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;



General

Ceiling | Track

tilt max 90°

rotation 355°

white | RAL 9016 <sup>1</sup>

IP20

3200 lm

LED

3000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 | R<sub>f</sub>: 92 | R<sub>t(1-15)</sub>: 93

MR 0.61 | MDER 0.55

Optical

flood | beam angle 40°

Electrical

DALI-2

PC2 | 220-240 V


system 23.4 W

system 137 lm/W <sup>2</sup>

Physical


diameter 110 mm | height 110 mm

## Light distribution



flood 40°			
h (m)	EO° (lx)	ø (m)	
1	6010	0.73	
2	1500	1.46	
3	670	2.18	
4	380	2.91	
5	240	3.64	

## Product drawing



## Installation instructions



## Lighting calculator



# VARO 110 S

track  
180-6530037F



Project / Type

Notes

Count / Date

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.975	0.944	0.913	0.883	0.854
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF <sup>a</sup>	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF <sup>a</sup>	Luminaire Maintenance Factor		LSF	Lamp Survival Factor	

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Optical accessories

### HONEYCOMB LOUVER

Ø (MM)  
106

ARTICLE NUMBER(S)  
080-6501118



### WIDE FLOOD LENS

Ø (MM)  
106

ARTICLE NUMBER(S)  
080-6502110W



### OVAL LENS

Ø (MM)  
106

ARTICLE NUMBER(S)  
080-6502210



### SNOOT short

Ø (MM)  
97

ARTICLE NUMBER(S)  
080-6503118



### SNOOT medium

Ø (MM)  
97

ARTICLE NUMBER(S)  
080-6503218



### SNOOT angle

Ø (MM)  
97

ARTICLE NUMBER(S)  
080-6503318

