

VARO 110 S

180-6530017F



Project / Type

Notes

Count / Date



220-240V

355°

X-PERT

X-PERT

General

Ceiling , Track

tilt max 90°

rotation 355°

white , RAL9016 ¹

IP20

3200 lm

LED

3000 K

CRI ≥ 90

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_f: 92 , R₍₁₋₁₅₎: 93

MR 0.61

MDER 0.55

Optical

flood

beam angle 40°

Electrical

non DIM

23.4 W

PC2 220-240V

137 lm/W

Physical


diameter 110 mm

height 110 mm

¹ RAL code

Track light made of die-cast aluminium; surface white powder coated; 355° rotatable and 90° tiltable; integrated converter in the plastic adapter; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; including high quality aluminium reflector with spherical reflector; high gloss anodised; neutral colour reflection through absolute freedom from interference colour; for brilliant object staging; precise radiation characteristic with 40° beam; installed and exchanged without tools; optical attachments available as accessories; optical attachments can be combined; accessories are listed separately; degree of protection IP20; PC2 220-240V; incl. converter, non dimmable; adapter for toolless insertion or movement on a variety of 3-phase power tracks; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Light distribution



flood 40°

| h (m) | EO° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 6010 | 0.73 |
| 2 | 1500 | 1.46 |
| 3 | 670 | 2.18 |
| 4 | 380 | 2.91 |
| 5 | 240 | 3.64 |

Product drawing



Installation instructions



Lighting calculator



[“180-6530017F”] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

VARO 110 S

180-6530017F



Project / Type

Notes

Count / Date

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|------------------------------|--------|-------------------|---------------------------------|--------|
| LLMF | 0.975 | 0.944 | 0.913 | 0.883 | 0.854 |
| LSF | 1 | 1 | 1 | 1 | 1 |
| MF | LMF × RSMF × LLMF × LSF | | RSMF ^a | Room Surface Maintenance Factor | |
| MF | Maintenance Factor | | LLMF | Lamp Lumens Maintenance Factor | |
| LMF ^a | Luminaire Maintenance Factor | | LSF | Lamp Survival Faktor | |

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Optical accessories

HONEYCOMB LOUVER

| Ø (MM) | ARTICLE NUMBER(S) |
|--------|-------------------|
| 106 | 080-6501118 |

WIDE FLOOD LENS

| Ø (MM) | ARTICLE NUMBER(S) |
|--------|-------------------|
| 106 | 080-6502110W |

OVAL LENS

| Ø (MM) | ARTICLE NUMBER(S) |
|--------|-------------------|
| 106 | 080-6502210 |

SNOOT

| TYPE | Ø (MM) | ARTICLE NUMBER(S) |
|--------|--------|-------------------|
| short | 97 | 080-6503118 |
| medium | 97 | 080-6503218 |
| angle | 97 | 080-6503318 |

