

ARY cable suspended 2 lamps

MOVE IT PRO

086-73100377M



Project / Type

Notes

Count / Date



General

Ceiling | Track Suspended

white | RAL 9016 ¹

Converter Traffic White

IP20

2040 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 98 | R_r: 91 | R₁₋₁₅: 89

MR 0.62 | MDER 0.56

Optical

medium | beam angle 25°

PstLM ≤ 1.0² ³ | SVM ≤ 0.4² ³

Electrical

DALI-2 | 1 DALI Addr.

PC2 | 220-240 V

system 28.2 W

system 72 lm/W ⁴

Physical

cable 2000 mm

diameter 47 mm | height 110 mm

adapter 402 mm


¹ RAL code ² combined

³ Value of containing product at full load (undimmed)

⁴ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Decorative pendant light inset made of aluminium; 2 lamps; cylindrical spotlight heads; surface white powder coated; light inset, incl. high power adapter + converter can be installed flexibly and without tools; power supplied via MOVE IT PRO system track profile; pendant fitting with 2000mm suspension, incl. feed (white), can be individually shortened; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2; 220-240 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Light distribution



medium 25° combined

h (m)	E0° (lx)	ø (m)
1	8820	0.44
2	2210	0.89
3	980	1.33
4	550	1.78
5	350	2.22

Product drawing



Installation instructions

