

ARY cable suspended 3 lamps

MOVE IT PRO

086-73202377F



Project / Type

Notes

Count / Date



General

Ceiling | Track Suspended

white | RAL 9016 ¹

Converter Traffic White

IP20

3410 lm

LED

3500 K

CRI \geq 90

L80 / 50000 h

initial MacAdam \leq 3 SDCM

R_g: 97 | R_f: 89 | R_{f(1-15)}: 87

MR 0.71 | MDER 0.64

Optical

flood | beam angle 44°

PstLM \leq 1.0² 3 4 5 6 | SVM \leq 0.4² 3 4 5 6

Electrical

DALI-2 | 1 DALI Addr.

PC2 | 220-240 V

system 41 W

system 83 lm/W ⁷

Physical

cable 2000 mm

diameter 47 mm | height 110 mm

adapter 402 mm

¹ RAL code ² combined ³ wallwasher lens BO 45 007-1965780


⁴ oval lens BO 45 007-1965880 ⁵ soft lens BO 45 007-1965980

⁶ Value of containing product at full load (undimmed)

⁷ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Decorative pendant light inset made of aluminium; 3 lamps; cylindrical spotlight heads; surface white powder coated; light inset, incl. high power adapter + converter can be installed flexibly and without tools; power supplied via MOVE IT PRO system track profile; pendant fitting with 2000mm suspension, incl. feed (white), can be individually shortened; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3500 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 44° beam; degree of protection IP20; PC2; 220-240 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Light distribution



flood 44° combined

h (m)	E0° (lx)	ø (m)
1	6320	0.82
2	1580	1.64
3	700	2.45
4	400	3.27
5	250	4.09

Product drawing



Installation instructions



Lighting calculator



[086-73202377F] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

16.06.2025