

# ARY cable suspended 1 lamp

MOVE IT PRO  
086-73002388M



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

black , RAL9005 <sup>1</sup>

Converter Jet Black

IP20

1520 lm

LED

3500 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 97 , R<sub>r</sub>: 89 , R<sub>t(1-15)</sub>: 87

MR 0.71

MDER 0.64

Optical

Medium

beam angle 25°

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

Electrical

DALI-2

14.1 W

PC2 220-240V

108 lm/W

1 DALI Addr.

Physical

cable 2000 mm


diameter 47 mm

height 110 mm

402 (adapter) mm

Decorative pendant light inset made of aluminium; 1 lamp; cylindrical spotlight head; surface black powder coated; light inset, incl. high power adapter + converter can be installed flexibly and without tools; power supplied via MOVE IT PRO system track profile; pendant fitting with 2000mm suspension, incl. feed (black), can be individually shortened; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3500 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2 220-240V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


## Light distribution



medium 25°

h (m)	E0° (lx)	ø (m)
1	6570	0.44
2	1640	0.89
3	730	1.33
4	410	1.78
5	260	2.22

## Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

