

ARY cable suspended 1 lamp

MOVE IT PRO

086-73002377M



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Track Suspended _____

white , RAL9016 ¹ _____

Converter Traffic White _____

IP20 _____

1520 lm _____

LED

3500 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 97 , R_r: 89 , R_{r(1-15)}: 87 _____

MR 0.71 _____

MDER 0.64 _____

Optical

Medium _____

beam angle 25° _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____

14.1 W _____

PC2 220-240V _____

108 lm/W _____

1 DALI Addr. _____

Physical

cable 2000 mm _____


diameter 47 mm _____

height 110 mm _____

402 (adaptr) mm _____

Decorative pendant light inset made of aluminium; 1 lamp; cylindrical spotlight head; surface white powder coated; light inset, incl. high power adapter + converter can be installed flexibly and without tools; power supplied via MOVE IT PRO system track profile; pendant fitting with 2000mm suspension, incl. feed (white), can be individually shortened; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3500 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2 220-240V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Light distribution



medium 25°

h (m)	E0 ³ (lx)	ø (m)
1	6570	0.44
2	1640	0.89
3	730	1.33
4	410	1.78
5	260	2.22

Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

