

ARY cable suspended 1 lamp

MOVE IT PRO

086-73001388M



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

black , RAL9005 ¹

Converter Jet Black

IP20

1560 lm

LED

4000 K

CRI \geq 90

L80 / 50000 h

initial MacAdam \leq 3 SDCM

R_g: 96 , R_r: 89 , R_{t(1-15)}: 89

MR 0.84

MDER 0.76

Optical

Medium

beam angle 25°

PstLM \leq 1.0 ²

SVM \leq 0.4 ²

Electrical

DALI-2

14.1 W

PC2 220-240V

111 lm/W

1 DALI Addr.

Physical

cable 2000 mm

diameter 47 mm

height 110 mm

402 (adapter) mm



Decorative pendant light inset made of aluminium; 1 lamp; cylindrical spotlight head; surface black powder coated; light inset, incl. high power adapter + converter can be installed flexibly and without tools; power supplied via MOVE IT PRO system track profile; pendant fitting with 2000mm suspension, incl. feed (black), can be individually shortened; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2 220-240V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Light distribution



medium 25°

h (m)	E0° (lx)	ø (m)
1	6750	0.44
2	1690	0.89
3	750	1.33
4	420	1.78
5	270	2.22

Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

