# **ARY** cable suspended 1 lamp

MOVE IT PRO

086-73000377F

Project / Type

Notes

Count / Date

220-240 V | X-PERT | X-PERT

Decorative pendant light inset made of aluminium; 1 lamp; cylindrical spotlight head; surface white powder coated; light inset, incl. high power adapter + converter can be installed flexibly and without tools; power supplied via MOVE IT PRO system track profile; pendant fitting with 2000mm suspension, incl. feed (white), can be individually shortened; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 44° beam; degree of protection IP20; PC2; 220-240 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## General

Ceiling | Track Suspended
white | RAL 9016 [1]
Converter Traffic White
IP20
1090 lm

## LED

3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 3 SDCM
$R_g$: 98 | $R_f$: 91 | $R_{f\{1\text{-}15\}}$: 89
MR 0.62 | MDER 0.56

## Optical

flood | beam angle 44°
PstLM ≤ 1.0[2 3 4 5] | SVM ≤ 0.4[2 3 4 5]

## Electrical

DALI-2 | 1 DALI Addr.
PC2 | 220-240 V
system 14.1 W
system 77 lm/W [6]

## Physical

cable 2000 mm
diameter 47 mm | height 110 mm
adapter402 mm

[1] RAL code [2] oval lens BO 45 007-1965880
[3] wallwasher lens BO 45 007-1965780
[4] soft lens BO 45 007-1965980
[5] Value of containing product at full load (undimmed)
[6] incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Light distribution




flood 44°

| h (m) | E0° (lx) | ø (m) |
|---|---|---|
| 1 | 2020 | 0.82 |
| 2 | 510 | 1.64 |
| 3 | 220 | 2.45 |
| 4 | 130 | 3.27 |
| 5 | 80 | 4.09 |

## Product drawing




## Installation instructions

## Lighting calculator

['086-73000377F'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com