

NOBA 60 suspended 1 lamp

MOVE IT PRO
086-71002388W



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

jet black , RAL9005 ¹

Converter Jet Black

IP20

982 lm

LED

3500 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 97 , R_f: 90 , R_{f(1-15)}: 89

MR 0.7

MDER 0.63

Optical

Wide Flood

beam angle 67°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

DALI-2

10.0 W

PC2 220-240V

98 lm/W

1 DALI Addr.

Physical

length 60 mm

width 60 mm

height 60 mm

402 (adapter) mm

suspension 2000 mm


¹ RAL code ² Value of containing product at full load (undimmed)

Lighting calculator



Decorative pendant light inset made of aluminium; 1 lamp; surface jet black powder coated; light inset, incl. high power adapter + converter can be installed flexibly and without tools; power supplied via MOVE IT PRO system track profile; pendant fitting with 2000mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 3500 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 67°; no multiple shadows; degree of protection IP20; PC2 220-240V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	933	1.31
2	233	2.63
3	104	3.94
4	58	5.26
5	37	6.57

Product drawing

