

# NOBA 60 suspended 1 lamp

MOVE IT PRO

086-71002377W



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Track Suspended \_\_\_\_\_

traffic white , RAL9016 <sup>1</sup> \_\_\_\_\_

Converter Traffic White \_\_\_\_\_

IP20 \_\_\_\_\_

982 lm \_\_\_\_\_

## LED

3500 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 2 SDCM \_\_\_\_\_

R<sub>g</sub>: 97 , R<sub>f</sub>: 90 , R<sub>t(1-15)</sub>: 89 \_\_\_\_\_

MR 0.7 \_\_\_\_\_

MDER 0.63 \_\_\_\_\_

## Optical

Wide Flood \_\_\_\_\_

beam angle 67° \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

## Electrical

DALI-2 \_\_\_\_\_

10.0 W \_\_\_\_\_

PC2 220-240V \_\_\_\_\_

98 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

## Physical

length 60 mm \_\_\_\_\_

width 60 mm \_\_\_\_\_


height 60 mm \_\_\_\_\_

402 (adapter) mm \_\_\_\_\_

suspension 2000 mm \_\_\_\_\_

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)


## Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	933	1.31
2	233	2.63
3	104	3.94
4	58	5.26
5	37	6.57

## Product drawing



## Lighting calculator



[“086-71002377W”] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com