

TUBIN 60 CONEX

surface / suspended system


058-5039538C



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Surface
black , RAL9005 ¹
2870 lm/m
IP20
8430 lm

LED

3000 K
CRI \geq 80
L90 / 50000 h
initial MacAdam \leq 3 SDCM
MR 0.56
MDER 0.51

Optical

Clear Cover
PstLM \leq 1.0 ²
SVM \leq 0.4 ²

Electrical


DALI-2
70 W
PC1 220-240V
120 lm/W
24 W/m

Physical

length 2936 mm
width 60 mm
height 60 mm

Carrier profile made of extruded aluminium profile; converter integrated into luminaire housing; for continuous lighting systems; surface black powder coated; for wall-/ceiling surface mounting or suspended mounting (1500 mm cable suspension - oblique or straight - as an accessory); easy installation using ceiling clips (available as an accessory) or with integrated tool-less suspension height adjustment; freely positioned attachment to the luminaire; canopy for through wiring (available as an accessory); electrical connection of the luminaires via plug/socket system; connectors (L-, T- or X-shape) available as an accessory; luminaire connection rotatable around its own axis, which means that any spatial angle can be realized; light control via high quality lens system for maximum, homogeneous illumination; clear, cylindrical cover with linear prismatic optic; with gentle ceiling illumination; light colour 3000 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1 220-240V; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)