

MINO 60 direct / indirect high lumen ceiling /

suspended system
046-506163XZ



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

special colours

3970 lm/m

IP20

indirect 1920 lm

direct 2730 lm

total 4650 lm

LED

4000 K

CRI ≥ 80

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.65

Optical

Microprismatic

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Luminaire housing made of extruded aluminium profile; angular design; for continuous lighting systems; light tight final end caps made of aluminium (available as an accessory); no visible screws; surface special colours powder coated; for suspended mounting (1500 mm cable suspension as an accessory); with integrated tool-less suspension height adjustment; spring clip attachment to the luminaire; freely positionable; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; direct/indirect illumination characteristic; indirect light component with integrated PC boards for maximum, homogeneous ceiling illumination; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Electrical

DALI-2

35 W

PC1 220-240V

133 lm/W

1 DALI Addr.

30 W/m

Physical

trim

length 625 mm


width 625 mm

height 80 mm

2.49 kg

¹ Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation
instructions



Lighting
calculator

