

# MINO 60 direct / indirect high lumen ceiling /

suspended system  
046-5061517Z



Project / Type \_\_\_\_\_  
Notes \_\_\_\_\_  
Count / Date \_\_\_\_\_



## General

Ceiling , Suspended  
white , RAL9010 <sup>1</sup>  
3490 lm/m  
IP20  
indirect 1690 lm  
direct 2400 lm  
total 4090 lm

## LED

3000 K  
CRI ≥ 80  
L90 / 50000 h  
photobio. safety RG 0 - no Risk  
initial MacAdam ≤ 3 SDCM  
MR 0.56  
MDER 0.51

## Optical

Microprismatic  
PstLM ≤ 1.0 <sup>2</sup>  
SVM ≤ 0.4 <sup>2</sup>

## Electrical

non DIM  
35 W  
PC1 220-240V  
117 lm/W  
30 W/m


## Physical

trim  
length 625 mm  
width 625 mm  
height 80 mm  
2.49 kg

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

Luminaire housing made of extruded aluminium profile; angular design; for continuous lighting systems; light tight final end caps made of aluminium (available as an accessory); no visible screws; surface white powder coated; for suspended mounting (1500 mm cable suspension as an accessory); with integrated tool-less suspension height adjustment; spring clip attachment to the luminaire; freely positionable; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; direct/indirect illumination characteristic; indirect light component with integrated PC boards for maximum, homogeneous ceiling illumination; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. converter, non dimmable; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

