

MINO 60 direct / indirect high lumen ceiling /

suspended system
046-5026617Z



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Suspended _____

white , RAL9010 ¹ _____

4420 lm/m _____

IP20 _____

indirect 4470 lm _____

direct 3280 lm _____

total 7750 lm _____

LED

4000 K _____

CRI ≥ 80 _____

L90 / 50000 h _____

photobio. safety RG 0 - no Risk _____

initial MacAdam ≤ 3 SDCM _____

MR 0.72 _____

MDER 0.65 _____

Optical

Microprismatic _____

UGR < 19 _____

PstLM ≤ 1.0 ² _____

Electrical

non DIM _____

55 W _____

PC1 220-240V _____

141 lm/W _____

31 W/m _____

Physical

trim _____

length 1756 mm _____


width 60 mm _____

height 80 mm _____

5.8 kg _____

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator



[“046-5026617Z”] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com