

# MINO 60 direct / indirect high lumen ceiling /

suspended system  
046-5025618Z



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



### General

Ceiling , Suspended \_\_\_\_\_

black , RAL9005 <sup>1</sup> \_\_\_\_\_

3980 lm/m \_\_\_\_\_

IP20 \_\_\_\_\_

indirect 2400 lm \_\_\_\_\_

direct 3420 lm \_\_\_\_\_

total 5820 lm \_\_\_\_\_

### LED

4000 K \_\_\_\_\_

CRI ≥ 80 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

photobio. safety RG 0 - no Risk \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

MR 0.72 \_\_\_\_\_

MDER 0.65 \_\_\_\_\_

### Optical

Microprismatic \_\_\_\_\_

UGR < 19 \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

### Electrical

non DIM \_\_\_\_\_

44 W \_\_\_\_\_

PC1 220-240V \_\_\_\_\_

132 lm/W \_\_\_\_\_

30 W/m \_\_\_\_\_

### Physical

trim \_\_\_\_\_

length 1464 mm \_\_\_\_\_


width 60 mm \_\_\_\_\_

height 80 mm \_\_\_\_\_

5.8 kg \_\_\_\_\_

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

### Light distribution



### Product drawing



### Installation instructions



### Lighting calculator

