

MINO 60 direct / indirect high lumen ceiling /

suspended system
046-502551XZ



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

special colours

3500 lm/m

IP20

indirect 2110 lm

direct 3000 lm

total 5110 lm

LED

3000 K

CRI ≥ 80

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.56

MDER 0.51

Optical

Microprismatic

UGR < 19

PstLM ≤ 1.0 ¹

Electrical

non DIM

44 W

PC1 220-240V

116 lm/W

30 W/m

Physical

trim

length 1464 mm


width 60 mm

height 80 mm

5.8 kg

¹ Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator



[“046-502551XZ”] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com